

TL30-D SERIES

Features



- High voltage track mounting and suspending install ways solution.

-Workable on International universal track brand,e.g Global, Suff, Nordic,etc.

- Multiple length solution for fleixibility.

-Max 180lm/W optional, energy and power cost-saving.



RoHS



General

- Indoor
- Aluminum housing
- Track mounted/Pendant
- Black/ White
- Power coated

Optic

- 60°/90°/110°/Double asymmetric25°
- UGR<23

90°

wide




60°

narrow



110°

Extremely wide



DS

Double asymmetric




Electrical

- Class I EU
- Driver type: constant current
- Input: 220-240VAC, 50Hz
- Power: 30/40/60W/75W
- PF: 0.9
- on/off, 0-10V,Triac,Dali


Photometric

- LED type: SMD 2835
- LED brand: Sanan
- SDCM<5
- CRI 80 (CRI90 optional)
- CCT: 3000K/4000K/5000K/6500K

Track type




STAFF




NORLUX




NORDIC



GLOBAL



Nuco



Other

Parameters

Part No.	L*W*H (mm)	Watt (W)	Voltage	Ra	Beam Angle option	Efficiency (lm/W)	Lumen @4000K (LM)
TL30-D5730- -8XX	L577*W33*H40 mm	DIP switch, up to 30W	AC220- 240V	80	60°/90°/110° Double asymmetric25°	130lm/W	3900
						150lm/W	4500
						180lm/W	5400
TL30-D1140- 8XX	L1150*W33*H40 mm	DIP switch, up to 40W	AC220- 240V	80	60°/90°/110° Double asymmetric25°	130lm/W	5200
						150lm/W	6000
						180lm/W	7200
TL30-D1460- 8XX	L1437*W33*H40 mm	DIP switch, up to 60W	AC220- 240V	80	60°/90°/110° Double asymmetric25°	130lm/W	9750
						150lm/W	11250
						180lm/W	13500
TL30-D1475- 8XX	L1437*W33*H40 mm	DIP switch, up to 75W	AC220- 240V	80	60°/90°/110° Double asymmetric25°	130lm/W	9750
						150lm/W	11250
						180lm/W	13500

