




MUSELED PRO ∞

LED NEON FLEX SPECIFICATION NT2020



Features:



-Big emitting size to 20mm,700lm/m high lumen.

-24VDC 10m running by one end power.

-Free cut on mono white,

-Versatile Installation: Comprehensive accessory system for flexible mounting in various scenarios.



Inspiration:

Versatile architecture lighting

- Commercial building
- Residential buildings
- Shopping mall
- Hotel





Electrical and photometric parameter:

Model NO.	CCT	CRI	Input Voltage	Current (A/m)	Power (W/m)	Lumen (lm/m)	Size (mm)	Length (mm)	Cutting Unit(mm)
NT2020-24-F9XX	2300K	>90	24VDC	0.4	9.6	600	W20* H20	10000	Free cut
	2700K					650			
	3000K					700			
	4000K					700			
NT2020-24-0X	R	/				5000		50	
	G								
	B								
	Y								


Note:

- 1. The above parameters are tested based on 1M standard products.
- 2. There is an allowable error range of ±10% for power and luminous flux.
- 3. All the above parameters are typical values.








Light Distribution



Technical Solution

Shadowless End Cap	Outlet	Suitable type	Suitable cables
	Side	Mono color	Silicone material, round wire, outer diameter 5.5-6.0mm
	Bottom	Mono color/RGB/RGBW/CCT	
	Top	Mono color/RGB/RGBW/CCT	

Accessories



Product name	Model NO.	Dimension	Description	Photo
Top outlet end cap	AC-NT2020ECT		Dimension : L16*W22.4*H22.4mm, Hole diamter: inside=6mm,outside=9mm	
Side outlet end cap	AC-NT2020ECS		Dimension: L19.5*W22.4*H22.4mm, Hole diamter: inside=6mm,outside=9mm	
End cap	AC-NT2020EC		Dimension : L16*W22.4*H22.4mm	
Alu install clip	AC-NT2020A-30		Lenght: 30mm Size: : W22.2*H21.65mm, Materilas: Alu	
Alu install carrier	AC-NT2020A-1000		Lenght: 1000mm Size: W22.2*H21.65mm, Materilas: Alu	
Modable groove	AS-NT2020M-1000		Length : 1000mm Size : W20.2*H16.4mm Materials : stainless steel	

Package

Model NO.	Product Dimension	Qty per inner box	Qty per carton	Product N.W/pc (Kg)	N.W/ CTN (Kg)	G.W/ CTN (Kg)	Carton dimensio (M)
NT2020-24-9XX	L5000*16*16	5m*1	40m	2.2	17.6	18.6	0.56*0.56*0.18
NT2020-24-0X	L5000*16*16	5m*1	40m	2.2	17.6	18.6	0.56*0.56*0.18

Precautions

Top bending
Minimum bending diameter > 140mm



Do not bend the lamp body left or right to avoid damaging the internal light strip



Do not twist the lamp body to avoid damaging the internal light strip

Precautions

1. This product is a low-voltage one. Please use a DC constant voltage isolated power supply to drive the LED light strip.
2. In practical applications, a 20% margin should be reserved for constant voltage power supplies (it is recommended to use only 80% of the power) to ensure sufficient voltage to drive the product.
3. Using the light strips beyond the standard cascading length will lead to phenomena such as overloading, overheating, voltage drop and uneven brightness.
4. It is strictly prohibited to use any acidic or alkaline adhesives to fix the products (including but not limited to glass glue, etc.).
5. IP67 is not suitable for immersion environments.
6. Under the same color temperature value, products of different sizes may have slightly different final colors due to structural differences. Please check the physical sample before use.